



The MWXP wide crown stapler is lightweight and well balanced, minimizing operator fatigue. Has excellent power, speed to handle the most demanding applications.

Applications:

For butt joints, lathing, insulation, and belt line attachment on mobile homes. Felt applications & foam insulation in building construction. Corrugated carton to skid, furniture & cabinet frames.

Features and Benefits:

- Five year limited warranty, XtremePro™ designed
- High load capacity (140 plus staples)
- Special wearplate and hardened safety
- EZ-clear™ latch provides quick and easy clearing of occasional jams

Choose the right trigger system for your specific needs!

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.


Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how SENCO will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: www.senco.com

Tool Specifications:

Item #: 120120N Contact Actuation (Dual Action)
 Weight: 7.4 lbs. (3.35 kg)
 Height: 9 ¾" (247.6 mm)
 Length: 12 ½" (317.5 mm)
 Staple Capacity: 140+
 Operating Pressure: 80-120 psig
 Mode of Operation: Tool is available with either sequential or contact actuation trigger mechanism
 Hose Fitting: ¾" NPT

Fastener Specifications:

Crown 1" (25.4 mm)
 Width: .062 (1.6 mm)
 Thickness: .055 (1.4 mm)
 Capacity 140+
 Staples: Drives 16 ga. staples from ¾" (19 mm) - 1 ½" (38 mm)



Length	Item Code	Carton Count	Finish
¾"	P11BAB	10.0M	Galv
7/8"	P12BAB	10.0M	Galv
1"	P13BAB	10.0M	Galv
1¼"	P15BAB	10.0M	Galv
1½"	P17BAB	10.0M	Galv
¾"	P11BABB	10.0M	Galv Band Line
7/8"	P12BABB	10.0M	Galv Band Line
1"	P13BABB	10.0M	Galv Band Line
1¼"	P15BABB	10.0M	Galv Band Line
1½"	P17BABB	10.0M	Galv Band Line
¾"	P11BPE	10.0M	Standard Galv
1"	P13BGBN	5.0M	Stainless

